

# Genuine TYM Snow Blowers Premium Version

Scrape It. Throw It. Clear the Way.



**TYM tractors are built for year-round performance—even in the harshest winter conditions.**

When the snow starts to fall, be ready with a genuine TYM snow blower. Designed to clear large areas with speed, efficiency, and precision, TYM snow-clearing solutions give you the confidence to take on heavy snowfall and keep moving all winter long.

## Choose the Right Snow-Clearing Solution

With **Premium Front-and Rear-Mount Snow Blower Options, Angular Blades, and Snow Pushers** TYM offers solutions to match your property, conditions, and clearing needs.

## Snow Blower Benefits:

- Direct the snow where you want it with the rotating chute.
- Adjust the clearing height to scrape surfaces clean or work just above gravel and pavement.
- Save time and effort while keeping driveways, paths, and large areas clear.
- Tackle heavy snowfall with confidence and keep your property accessible throughout the season.

| DESCRIPTION                 | MODEL NAME | APPLICABLE TRACTOR         |
|-----------------------------|------------|----------------------------|
| 50" Front Mount Snow Blower | 150FM      | T224 (T1022), T254 (T1025) |
| 60" Front Mount Snow Blower | 160FM      | T2025P                     |
| 5' Snow Pusher*             | 15SP       | T224 (T1022), T254 (T1025) |
| 5' Backdrag Kit*            | 15SP-BD    | T224 (T1022), T254 (T1025) |
| 6' Snow Pusher*             | 16SP       | T2025P                     |
| 6' Backdrag Kit*            | 16SP-BD    | T2025P                     |
| 7' Snow Pusher*             | 17SP       | T3025, T3035               |
| 7' Backdrag Kit*            | 17SP-BD    | T3025, T3035               |
| 54" Snow Blade*             | 154BLD     | T224 (T1022), T254 (T1025) |
| 66" Snow Blade*             | 166BLD     | T2025P                     |
| 50" 3PT Snow Blower*        | 150SE      | T224 (T1022)               |
| 60" 3PT Snow Blower*        | 160SE      | T254 (T1025)               |
| 66" 3PT Snow Blower*        | 166SE      | T2025P                     |

\* 2-month lead time

# Snow Blower Specifications

## Front Mount Snow Blower

**Features:** PTO-powered, two-stage snowblower, Operator friendly snowblower tractor kit design, Best in class sectional flighting, Bolt on cutting edge, Standard hydraulic chute rotation, 4-point adjustable skid shoes

| Model                  | 150FM                      | 160FM     |
|------------------------|----------------------------|-----------|
| Applicable Tractor     | T224 (T1022), T254 (T1025) | T2025P    |
| PTO HP                 | 15hp                       | 20hp      |
| Cutting Width          | 50”                        | 60”       |
| Cutting Edge           | 3/8” x 3”                  | 3/8” x 3” |
| Auger Diameter         | 12”                        | 12”       |
| Fan Diameter           | 16”                        | 16”       |
| Fan Blades             | 4                          | 4         |
| Chute Diameter         | 5.5”                       | 5.5”      |
| Chute Rotation         | Hydraulic                  | Hydraulic |
| Chute Deflector        | Manual                     | Manual    |
| Main Body Height       | 24"                        | 24”       |
| Main Body Weight       | 420 lbs                    | 435 lbs   |
| Tractor bracket weight | 48 lbs                     | 48 lbs    |

## 3PT Snowblowers

**Features:** 540 PTO, Shear bolt protection, Adjustable /Replaceable skid plates

| Model                    | 150SE        | 160SE        | 166SE     |
|--------------------------|--------------|--------------|-----------|
| Applicable Tractor       | T224 (T1022) | T254 (T1025) | T2025P    |
| PTO HP                   | 15hp         | 20hp         | 25hp      |
| Width                    | 50”          | 60”          | 66”       |
| Cutting Edge             | 3/8” x 3”    | 3/8” x 3”    | 3/8” x 3” |
| Auger Diameter           | 14”          | 14”          | 14”       |
| Fan Diameter             | 19”          | 19”          | 19”       |
| Fan Blades               | 4            | 4            | 4         |
| Hydraulic Chute Rotation | Optional     | Optional     | Optional  |
| Chute Deflector          | Manual       | Manual       | Manual    |
| Main Body Height         | 23.25”       | 23.25”       | 23.25”    |
| 3PH Mount                | Cat. 1       | Cat. 1       | Cat. 1    |
| Weight                   | 440 lbs      | 530 lbs      | 593 lbs   |

## Front Mount Snow Pusher\*

\* 2-month lead time

| Model               | 15SP                       | 16SP                      | 17SP                      |
|---------------------|----------------------------|---------------------------|---------------------------|
| Applicable Tractor  | T224 (T1022), T254 (T1025) | T2025P                    | T3025, T3035              |
| Cutting Width       | 60”                        | 72”                       | 84”                       |
| Height              | 30”                        | 30”                       | 30”                       |
| Cutting Edge        | GR50 1/4” x 6” reversible  | GR50 1/4” x 6” reversible | GR50 1/4” x 6” reversible |
| Back Drag           | Optional                   | Optional                  | Optional                  |
| Horsepower Range    | Up to 55hp                 | Up to 55hp                | Up to 55hp                |
| Skid Shoes          | 1/4” x 2 replaceable       | 1/4” x 2 replaceable      | 1/4” x 2 replaceable      |
| Moldboard Thickness | 7 Ga.                      | 7 Ga.                     | 7 Ga.                     |
| Sidewall Thickness  | 7 Ga.                      | 7 Ga.                     | 7 Ga.                     |
| Blade Marker        | Mounting holes provided    | Mounting holes provided   | Mounting holes provided   |
| Weight              | 360 lbs                    | 380 lbs                   | 400 lbs                   |

## Front Mount Snow Blade\*

\* 2-month lead time

| Model                       | 154BLD                     | 166BLD                    |
|-----------------------------|----------------------------|---------------------------|
| Applicable Tractor          | T224 (T1022), T254 (T1025) | T2025P                    |
| Cutting Width               | 54”                        | 66”                       |
| Cutting Width at 30 Deg     | 46”                        | 60”                       |
| Max Blade Tilt Angle        | 30 degrees right, 30 left  | 30 degrees right, 30 left |
| Moldboard Height with Blade | 16”                        | 16”                       |
| Cutting Edge                | GR50 1/4” x 6” reversible  | GR50 1/4” x 6" reversible |
| Horsepower Range            | Up to 55hp                 | Up to 55hp                |
| Springs                     | 2                          | 2                         |
| Skid Shoes                  | Standard                   | Standard                  |
| Moldboard Thickness         | 7 Ga.                      | 7 Ga.                     |
| Spring Trip Load            | 1000 lbs                   | 1000 lbs                  |
| Blade Marker                | Mounting holes provided    | Mounting holes provided   |
| Weight                      | 300 lbs                    | 325 lbs                   |